



Snowpulse SA
Case Postale 373
1936 Verbier
Switzerland
www.snowpulse.com
info@snowpulse.com

User guide of Snowpulse “Life Bag”

1.	Introduction.....	2
2.	Read carefully: Awareness related to avalanche risks.....	3
3.	Global awareness	4
4.	Information related to the use of a cylinder filled with compressed air	5
5.	Quick Start.....	7
6.	Operating instructions.....	8
7.	Instructions for use	13
8.	Maintenance, Storage, and Cleaning	15
9.	Cylinder transport	16
10.	Troubleshooting.....	17
11.	Warranty	18
12.	Technical data.....	19
13.	Specifications.....	19
14.	Components	20

1. Introduction

Congratulations on your purchase of the Snowpulse “Life Bag”. The “Life Bag” provides you a greater degree of safety in the mountains without compromising the weight or volume of your backpack.

Avalanches kill people each year. The Snowpulse «Life Bag» will increase your chances of survival; however the Snowpulse «Life Bag» does NOT guarantee your safety during an avalanche. Snowpulse airbags are rescue devices, like avalanche beacons, avalanche probes, and avalanche shovels. You must not take more risks just because you have a Snowpulse airbag!

Snowpulse airbags have 2 main purposes:

1. The first one is to keep an avalanche victim on the surface, facing upward with the head above the snow. This is possible using the inverse segregation, a phenomenon that results in the bigger particles of a fluid in motion being on the surface after a certain amount of time. To be efficient, avalanche airbags need be sweep along within the avalanche flow.
2. The second purpose is to protect the head and the thorax during an avalanche. Trauma protection is provided as soon as the airbag is inflated. To ensure the efficiency of your airbag, it is important that the airbag is deployed as soon as you are caught in an avalanche or believe you may be caught in one.

The “Life Bag”, developed by Snowpulse SA, has several key innovations:

- A floatation Head On Top which encourages an upward facing position with the head above the snow
- Protection of the head and thorax (15-20% of avalanche deaths are due to trauma)
- A light and compact system
- A quick-fastening buckle
- An easy-to-reuse system without having to return your “Life Bag”
- A easy refill/exchange of the air cylinder (see conditions within this manual)
- The correct use of the Snowpulse “Life Bag” relies on the system being in good condition and the user being trained. The handling and instructions provided within this user guide should be carried out carefully.

2. Read carefully: Awareness related to avalanche risks

Read before use. Do not throw away instructions:

- Snowpulse airbags cannot prevent avalanches.
- An avalanche always presents a risk of death or injury, with or without an airbag.
- The Snowpulse Company is not liable for any injury or death resulting from an avalanche.
- Any person practicing an activity and using a Snowpulse airbag agrees to do so at his own risk.
- The use of a Snowpulse airbag should not increase the risks taken.
- The best protection from an avalanche is to not put yourself in avalanche terrain. If in doubt, do not proceed.
- The Snowpulse airbag attempts to hinder victim burial, among other things. There are, however, situations in which the effectiveness of the airbag could be limited, and burial is possible.
- The Snowpulse airbag does not offer any assistance in searching for a victim completely buried by an avalanche. Searching for a buried victim is only possible using an avalanche transceiver. .
- The Snowpulse airbag is a safety supplement, such as an avalanche transceiver, probe, and shovel. These various tools are complementary and essential for safe backcountry travel
- The Snowpulse airbag must be deployed by the user himself. Users should train themselves and simulate pulling the handle in order to react quickly and effectively in the event of an avalanche.
- Snowpulse airbags require maintenance and proper storage.
- The overall condition of the system should be checked before each outing, following the instructions contained in the chapter, “Quick start Snowpulse”.

Snowpulse airbags and their backpacks are approved in accordance with the EC Directive 89/686 for PPE by the TÜV SUD Product service, Riderstr.65, D-80339 München, control n° 0123.

3. Global awareness

Read before use:


- All of the straps and components of the « Life Bag » have a role in the functioning of the airbag system should an avalanche occur. The straps and the buckles integrated into the «Life Bag» create a harness around the user and are an integral part of the «Life Bag» functioning correctly. **Do not change the buckles or straps on the «Life Bag» as it may result in a weakening of the product and as a result the airbag being ripped from the user during an avalanche.** Do not attempt to dismantle or modify any part of your airbag which is not described in the user manual. Any modification which is not described in the user manual can damage the system and put the user in jeopardy. Internal repair and trouble shooting must be done by a Snowpulse retailer. Any modification can void the warranty of the Snowpulse pack.
- To ensure proper functioning of the «Life Bag» the waist buckle, chest buckle, and leg straps must be fastened correctly every time you put it on. Ensure that all straps are snug around the user. Failure to use the leg strap may result in the Snowpulse rising up on the user during an avalanche which may lead to the chest strap choking the user.
- Ensure that all zippers are completely closed. It is very important that the zipper which runs over the shoulder of the user (and that close the cover containing the airbag) is zipped all the way and the slider is at the very bottom of the shoulder strap
- **Keep the "Life Bag" out of reach of children.** The "Life Bag" contains a cylinder of compressed air which poses a serious threat to a child or user if not treated properly.
- The « Life Bag » has been designed for 20 airbag deployments. Once the airbag has been deployed 20 times the «Life Bag» needs to be returned to the retailer to perform a check on the internal components of the «Life Bag».
- If the airbag gets wet, unfold the airbag to dry it out, and repack it once dry using the procedures outlined in the manual. This is important as a wet airbag can freeze and affect the deployment of the «Life Bag».
- The « Life Bag » must only be used to increase survival chances in the case of an avalanche. It is dedicated to winter activities in back country.
- The airbag should not be inflated on ski resort slopes as people may be surprised by its inflation and loose the control.
- Inflated, the airbag reduce the field of vision. Trigger of the airbag should therefore be done when this reduction does not represent a risk.

4. Information related to the use of a cylinder filled with compressed air

4.1. Awareness

The « Life Bag » uses a cylinder filled with compressed air. Improper handling of the cylinder could result in the cylinder exploding and raises a potential threat of injury or loss of life. Improper handling can also damage the "Life Bag" and its cylinder

Please use the following rules:



- The release mechanism on the top of the cylinder must not be manipulated or dismantled.
- Manipulation of the release mechanism (= cylinder valve) during a cylinder refill must only be done by trained individuals.
- Refill must be done by people having been officially trained and following the instruction provided during the training.
- Do not throw or damage the cylinder with tools (hammer, grips, etc...)
- Never expose the cylinder to heat (stove, direct sunlight, etc...), maximum temperature 50°C
- If you have an extra cylinder, or your cylinder is not installed in your life bag, keep it in its original packaging, with yellow thread protectors on, in a dry, cool, place.
- If you wish to mail a pressurized cylinder the carrier must be informed and all rules and regulations followed (as well for the destination country). Cylinders must be mailed only in their original package with their 2 yellow caps. See chapter 9 for more information.
- The cartridge can only be used if the 2 red tapes are on place and in good state. Those tapes avoid any water infiltration in the mechanism.

4.2. Working pressure

The work pressure of your cartridge is marked on it. The Snowpulse “Life Bag” is designed to work at temperatures between -30 C and + 50C. The pressure gauge on the top of the cylinder allows you to simply and continuously monitor the cylinder pressure. To function properly the cylinder is designed to be filled at 20°C (= 68°F), at which point the gauge needle should be in the “green” zone. At very cold temperatures the pressure needle will remain in the “blue” zone, and at high temperatures within the “red” zone,

A cylinder with a pressure of 3'000 PSI (American Cylinder) or 300 bar (European Cylinder) at a temperature of 20°C will ensure proper inflation of the airbag for temperature range of -30°C +50°C. A pressure below at 20°C will result in incomplete inflation of the airbag and will not provide the user any protection. Variations in temperature will change the pressure of the cylinder. At cold temperatures, it's normal that the gauge needle is in the blue area indicating a pressure lower than that checked at 20°C. This does not alter the function of the airbag.

Do not use if the pressure is over 3100 PSI (American Cylinder) or 310 BAR (European Cylinder) at 20°C as it could damage the system and injure the user.

4.3. Cylinder Exchange/Refill


After your «Life Bag» has been deployed the cylinder will need to be refilled. You can have your cylinder refilled or exchanged for a full one at several Snowpulse retailers and at specific dive shops throughout North America.

Only individuals who have gone through the training with a Snowpulse representative are authorized to refill the Snowpulse cylinders. The training is available to all organizations, as well as individual customers. Once the training is completed the user will require a source of dry compressed air (compressor or scuba tank) and specific attachments to refill the Snowpulse cylinders. Please visit www.snowpulse.com for more information.

5. Quick Start

This quick start is intended to give you a brief introduction into the features of the «Life Bag» needed to get started. To ensure the proper functioning of your Life Bag, it must be checked after purchase and thereafter prior to each outing. We also recommend that you carefully read the complete User Manual.


1. Check that the zip on the shoulder straps (which contains the airbag) and its Velcro patch are completely closed.
2. Check to ensure that all mechanical components are tightened.
3. Check the air cylinder pressure.
4. Check that the handle is correctly connected to the cylinder release pin.
5. Check that the cylinder is securely attached and that there are no objects jamming the air channels.
6. Before entering avalanche terrain, unzip the release handle from its pocket. Ensure that the chest strap does NOT go through the handle, and should the need arise the handle is in a good pulling position.
7. Do up your chest and waist buckle as well as the leg straps.
8. In case of an avalanche firmly pull the handle.



6. Operating instructions


System assembly can be carried out upon receiving the product, but also following its use, whether in the case of trial or actual avalanche.

6.1. Attaching the cylinder within the Snowpulse «Life Bag»:



1. Check the cylinder

Check the pressure as outlined in Chapter 4 and ensure that the cylinder appears in good condition.




2. Check that all cylinder components are tight



3. Check straps and buckles

Ensure that all straps and buckles, including the ones holding the cylinder, are in good shape. This should be checked on a regular basis throughout your trip.



4. Trigger cable check

Ensure that the handle is secured to the release cable and that the release cable passes freely through the outlined slit. Check also that the cable slide freely within the hose




5. Airbag folding (this is unnecessary upon receiving the airbag)

Follow the instruction and pictures contained in chapter 6.2. Folding of the airbag is required after deployment of the system (either for training purposes or in the case of an avalanche), if the airbag has not been deployed in more than 1 year, or if you suspect that the airbag is wet or moist. To avoid jamming the fabric while closing the zip, put your finger between the zip and the airbag fabric.



6. Closing of the airbag cover (unnecessary upon receiving the airbag)

Following a total or partial opening of the cover (unwished or due to airbag inflation), continue to completely undo the zipper. At this point bring back the zip slider from handle side to the other side. Then reclose the zip. The zip must be closed from the right shoulder to the handle side. It's mandatory to fully close this zip. For more details, see chapter 6.2.




7. Attaching the cylinder into the «Life Bag».

Unscrew the yellow thread protector on the top of the cylinder. Screw on the cylinder until the end of the threads, and then unscrew slightly if necessary, so that the filling connector is on your right and the guage is facing you. Do not unscrew more than one turn.

Warning: Always screw the cylinder in before removing the pin cover cap (the small one on the side). If tightening is met with abnormal resistance just clean the screw with an oiled tissue and try again. In case of problem contact your Snowpulse retailer.

8. Attaching the release cable

Warning: Use caution when attaching the cable to the release pin so that you do not accidentally deploy the «Life Bag». Unscrew the yellow thread protector. Screw the cable onto the release pin. Some resistance may be felt due to thread sealant on the pin. The connector must be screwed on 5mm and tightened well,




9. Attaching the cable hose connector onto the opening mechanism

The cable hose connector should be tightened securely onto the opening mechanism. This prevents any moisture entering the system, which could ice up and cause a malfunction.



10. Fastening the cylinder to the backpack:

Fasten the cylinder using the Velcro patch within the «Life Bag». Zip up the mesh pocket containing the cylinder.



11. Attaching the Handle


Use the Velcro to attach the handle. Wear and tear of the Velcro may mean that the handle has been poorly fastened. When transporting or storing your «Life Bag», zip the handle into the pocket. Be sure to take it out of the pocket before you proceed into the backcountry.

12. Check following Quick Start (Chapter 5)

Do a last check following instruction of chapter 5. Congratulation, your « Life Bag » is now ready to use

6.2. Airbag Folding Instructions

1. The folding of the airbag will be necessary after a deployment, if the airbag has got wet, been stored for more than one year, or if the zipper starts to come apart. To avoid jamming the fabric while closing the zip, put your finger between the zip and the airbag fabric. You do not want to roll the airbag. A refolding video can be found on the CD provided or on www.snowpulse.com. Push the long nylon rod inside your pack into the metal cone located above the cylinder. Keep this in place for the next few steps.
2. Ensure that the zip covering the airbag is completely apart. Bring back the zip slider to the side opposite the handle. Bring back the cover zip's slider from the handle side to the beginning of the zip. This is possible once the zip is completely split apart. To split apart the zip, ensure the zip slider is at then end of the zip (handle side) and gently pull on the 2 sides of the zip.
3. Place the pack down with the shoulder straps facing up. The airbag has four seams, align the top two with the bottom two.
4. Fold up the end of the airbag. Fold the sides in, starting with the side closest to the centre. Take care not to roll the sides in. Zip up the first 20-30cm. To avoid jamming the fabric while closing the zip, put your finger between the zip and the airbag fabric. On the handle side close the handle pocket over the airbag to hold it in place.
5. Fold up the top of the airbag
6. Push the top of the airbag into the mesh pocket contained at the top of the pack. Again be careful not to roll the airbag. Zip the cover closed placing a finger underneath the zipper to avoid jamming of the airbag fabric. Close the zipper all the way around, ensuring that zipper is completely closed.
7. Remove the nylon rod used to deflate the airbag.



7. Instructions for use

7.1. Adjusting the airbag to fit

Using the various straps adjusts the «Life Bag» to properly fit your body. It is very important that the «Life Bag» remain attached to the victim during an avalanche, and to do this all straps and buckles should be well fastened. The three main attachment points are the chest strap, waist belt, and leg strap. See the “Quick Start” portion of this user manual for figures. Snowpulse backpacks are designed to fit individuals of various sizes. The «Life Bag» is available in Medium and Long sizes, and 15L, 30L, and 45L volume packs. If the «Life Bag» does not fit your body, you should not use it.

7.2. Take care to avoid getting dust on the mechanical parts

The interior of the bag should not contain any loose, small particles such as bread crumbs and chips which could limit the effectiveness of the system when it is deployed. Take care to avoid getting dust, food, etc on the mechanical parts within the backpack.

7.3. Use of the release handle pocket

The release handle should always be stored in its pocket when you are transporting or not using the pack. This includes travelling on a ski lift or helicopter. This is to avoid unwanted deployment of the Snowpulse. Ensure that you open up the handle before entering avalanche terrain.

7.4. Carrying Skis, a snowboard, and other Gear

All of the outside straps on the «Life Bag» can be used to carry gear. However it is very important that the airbag cover located at the top of the pack is not blocked. Also take care not to carry any sharp objects on your shoulder. The shoulders on the Snowpulse «Life Bag» have been reinforced so that it is possible to carry skis over your shoulders, however the skis should be carried flat, not on their edges. If the black fabric containing the airbag has been cut, check carefully that the airbag fabric has not been damaged. The «Life Bag» 30L and 45L allows you to carry skis on the side or diagonally on your pack; snowboards are carried vertically.



7.5. Use of the system in the event of avalanche

In the event that you believe you are about to be caught in an avalanche deploy the «Life Bag» as soon as possible by pulling the trigger handle. The airbag inflates in approximately 2-3 seconds and makes a significant amount of noise. If you are able to do so, try to reach a safe location to avoid getting caught. It takes approximately 6Kg (13lbs) of force to deploy the airbag. After the «Life Bag» is deployed use the nylon rod inside of the airbag to completely deflate the airbag. Push the pin through the netting towards the interior of the airbag via a hole of the diffuser and then deflate the airbag. Once the airbag is deflated, fold the airbag as explained in this document. Once the airbag is folded and its cover closed, remove the tool used to deflate it. Poor folding or folding a wet airbag could cause malfunction of the system and/or damage it. After use of the system in a real avalanche, check all parts of the “Life Bag” to detect and identify any damage. Contact your retailer to evaluate if your “Life Bag” should be returned to the factory for quality control testing. A full cylinder now needs to be installed. The Snowpulse «Life Bag» cylinder is good for 1 deployment only before it needs to be refilled and serviced.

8. Maintenance, Storage, and Cleaning

8.1. Maintenance required annually or after moisture has penetrated the «Life Bag».

- Unfold the airbag to let it dry completely and refold it once it is completely dry.
- Check all cables and attachment points to make sure they are secure and in good condition.
- Check the overall condition of the «Life Bag» by following the checks outlined in the chapter “Quick start Snowpulse”.

8.2. Checks after an avalanche

Checks after an avalanche must be carried out with a great prudence since the airbag and the Snowpulse system could be seriously damaged or unusable. The airbag seals must be checked to avoid any risk of rips or tears which could leak. . Visual monitoring is essential to assess the general condition of the system (seams, straps, and mechanics). It is strongly recommended that you send your backpack to a Snowpulse retailer for a complete system check.

8.3. Checks after 20 deployments of the «Life Bag»

The « Life Bag » mechanism has been designed to allow 20 deployments of the airbag (either for training or for real use). Any Snowpulse «Life Bag» which has been deployed 20 times is required to be sent back to the Snowpulse dealer for a complete check of the product.

8.4. Storage and cleaning of the «Life Bag»

- **Keep the “Life Bag” out of reach of children.** The “Life Bag” and its cylinder of air under pressure can create serious injury to child or user
- Store the Snowpulse «Life Bag» in a dry, cool place.
- Cylinders not installed in the «Life Bag» must always be stored in its original packaging with the yellow thread protectors on
- Clean the Snowpulse «Life Bag» with water only, do not use any solvents.
- Be sure not to stress the bag or put heavy loads on it during transport.

9. Cylinder transport

For any shipment, the 2 yellow thread protectors must be in place. The cylinder must always be shipped within the Snowpulse pack or in its original packaging. Air transport according to the International Air Transport Association (IATA)

- Transport of a Snowpulse airbag with a European (300 bar) cylinder under pressure is allowed for private purpose but it is required that you declare the «Life Bag» before check-in. (norm OACI under the description of « Avalanche Rescue Backpack » reference: IATA-DGR. Table. 2.3. A). Despite air transport of the European cylinder is allowed regarding the IATA worldwide regulation, you must follow the regulation of your country; the European cylinder is for example not allowed in Canada nor USA. Following status of the regulation in 2008, the “Life Bag” with a full European cylinder is accepted for air transport in all Europe
- Transport of a Snowpulse airbag with an American (3000 PSI) cylinder under pressure is regulated and is allowed only for transport linked to rescue missions (and that for any country). Only in Canada the transportation of a Snowpulse «Life Bag» with the American Cartridge is allowed for air transportation as the system is classify as UN2990 LIFE-SAVING APPLIANCES, SELFINFLATING. This includes heli-skiing activities.

In all cases it is always possible to empty the cylinder by triggering the airbag. Never try to empty a cylinder by any other means than deploying the «Life Bag» using the trigger handle. Transport of an empty cylinder is not regulated.

9.1. Cylinder shipment

Freight companies must be made aware of the content of your shipment. It is your responsibility to respect the regulations within your country. In most cases it is required that if you are shipping a full cylinder it must properly labelled as a dangerous good. Below is a list of information which your carrier may require.

Snowpulse cylinders are a dangerous good according to the European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR).

ONU official number :

UN 1002

Official designation :

Compressed air, 2,

Official label :

2.2

Classification :

2

Small quantity notification :

Exemption : Transport not overpassing free limits described in chapter 1.1.3.6".

10. Troubleshooting

10.1. The airbag is not completely inflated.

Your airbag should be completely inflated when you pull the handle, and then over several minutes it should slowly deflate. This is normal if the airbag does not fully inflate there are several possible reasons: The airflow within the diffuser or air channel may be blocked. For the Snowpulse to work properly air must be able to freely pass through the air channel and diffuser. Make sure the internal mechanical components are free and not jammed. The mesh pocket containing the cylinder must never be used to store anything else. Check The cylinder pressure may be to low. A pressure below 3000PSI (American cylinder) or 30obar (European cylinder) for a cylinder at 20°C (=68°F)does not allow a complete inflation of the airbag. The pressure of your cylinder must be checked at 20°C.

- Check that no objects are blocking the airflow in the back air channel.
- The zip of the cover containing the airbag must be completely closed with its slider at the end of the zip, on the handle side.

10.2. Nothing happens when you pull the handle :

- Check that the cable is linking the handle to the release. Check both end of the cable are attached and in good condition.
- Check that the cylinder is not empty as indicated by the gauge.
- Check that the cable hose is securely fastened to the cylinder.
- To trigger the airbag, it's necessary to pull the cable with a force of approximately 6Kg (13lbs). Pull the handle in front of you rather than pulling down, the Velcro attaching the trigger handle should release..

If this does not solve the issue, return your «Life Bag» to the retailer with your receipt. The retailer will send the «Life Bag» to the distributor or to Snowpulse directly.

11. Warranty

This Snowpulse «Life Bag» has been extensively tested and researched, every detail has been looked at. The materials used are the most suitable for their intended use and a stringent quality control system helps to reduce the possibility that your «Life Bag» has any defects. The «Life Bag» comes with a 3 year, 100 days of use warranty.

- The guarantee does not cover defects caused by improper use or normal wear and tear of parts following prolonged use.
- The purchaser must return the faulty item to the point of sale where the purchase was made along with the proof of purchase (a condition required for the validity of the guarantee)
- The retailer will forward the item to the distributor or directly to Snowpulse
- Snowpulse will, at its discretion, replace or repair the item. If the defect is not covered by the warranty, repairs will be carried out at a low cost, inclusive of shipping or postage.
- This guarantee does not affect the consumer's statutory rights, as specified by the laws in force in the country of use.

Warning :

The « Life Bag » mechanism has been designed to allow 20 deployments of the airbag (either for training or real use). It is mandatory that your Snowpulse retailer do a complete check of your product after 20 deployments.

12. Technical data

Temperature range: -30°C to 40°C

Airbag volume: 150 litres

Inflation time: 3 sec (function of elevation and temperature)

Weight 15L, 30L 45L: 3 kg +/- 100g (without cylinder: 2.4kg)

Gas: breathable air (dry)

Cylinder pressure: see its label

13. Specifications

Type: Snowpulse Life Bag


Manufacturer: Snowpulse SA,
Place de Savoleyres,
Case Postal 373,
1936 Verbier,

Country manufacture: Switzerland


CE: directives PPE 89/686

Notified body : TÜV Sud Produkt Service
Ridlerstr.,65
D 80339 München
Notified body N°0123

14. Components



No.	Description
1	Cylinder frame
2	Gaz cylinder
3	Cylinder O-ring
4	Piston
5	Piston O-ring
6	Ring of piston
7	Support piston
8	Lever
9	Release pin
10	Pin for lever
11	Tightening ring
12	Connect Cable
13	Quick connector
14	Piston quick disconnect
15	Quick connector O-ring
16	Filter
17	Diffusor
18	Conduit
19	Valve
20	Valve Ring
21	Ring
22	2nd Ring
23	Ring to tight diffusor
24	Diffusor rubber
25	Hose connector
26	Hose
27	Cable
28	Spring



No.	Description
1	Trigger cable
2	Velcro to anchor the trigger handle
3	Trigger Handle
4	Cover zip's
5	Handle pocket
6	Cover over zip gap
7	Chest Buckle
8	Air input
9	Air input 2
10	Waist buckle
11	Leg strap
12	Hose-Cylinder connector
13	Diffusor
14	Release pin connector
15	Cylinder pocket
16	Nylon Rod to deflate airbag



This symbol means that the user guide must be read before this backpack is used.